

YK-L6030D+YK-LS6040 Bilateral sealing shrink packaging machine



Technology Data:

1. Machine Dimension (L*W*H): 1650*900*1550/1640*780*1625mm
2. Max Packing Size (L*W*H): Length no limit*W+H<(=)900mm, 1500*650*300mm
3. Net weight: 400/500kg
4. Tunnel Dimension (L*W*H): 1800*600*400mm
5. Packing Speed: 6-12 pcs/min
6. Cutter Size (L*W): 1000mm
7. Special Machine: Could Be Made

Control System:

1. Power: Motor: 4/22KW
2. Program: PLC, self-induction, adjustable rotary speed
3. Voltage/Power: 3PH 220/380V 50/60HZ

Operating Condition:

1. Air pressure: 6kg/cm²
2. Applicable film: PE/PE/PE
3. Height of work table: 850+(-)50/ 850+(-)50/ 850+(-)50

Quality Assure:

1. Get CE certification
2. Awarded the high-tech industry
3. First lever supplier of china automatic manufacturer
4. Has the world-class level of dynamic
5. Has good customer service

Application:

Our products have been widely applied to, chemical fiber, leveraging, oil refining, papermaking, electric power, power plant, metallurgy, food, pharmaceuticals, etc. Main products are sold primarily for domestic market and exports, for instants, Thailand, Canada, Mexico, India, etc.