



Sugar, Oral Saline and Granule Packing Machine DXDO-K900E



As shown in the picture, the granule packing machine is used for packing loose, non sticky granule materials in the medicine, food, daily chemical and other industries. It can be applied to measuring and automatic packing into sachets such materials as Chinese medicine infusion, oatmeal, coffee, etc., crystalline materials like monosodium glutamate, white sugar, salt, etc. and small shot materials like Chinese patent drugs, dryers and so on.

Note: This range of equipment is designed with filling capacity between 5 and 100ml. It is not suitable for occasions with filling volume exceeding 100ml.

Characteristics:

1. The sugar, oral saline and granule packing machine features advanced performance, high power, low noise, compact structure, and stable performance. It is easy to maintain and has a long life span.
2. This packing machine uses a five shaft servo motor in step driver and man-machine interface touch adjustment. Controlled by PLC, the granule packing machine is precise in automatic step positioning.
3. With a high degree of automation, the packaging machine can finish packing at one time from longitudinal sealing, longitudinal cutting, transverse sealing, filling, embossing, notch cutting, dotted line cutting, transverse cutting to outputting finished sachets.
4. The sugar, oral saline and granule packing machine uses high precision heat sealing rollers for sealing mold, with four-side sealing, and in multi-line sachet form. The machine provides high packing speed, neat, delicate and beautiful bags, and high packaging efficiency.
5. Easy and fast to adjust, the packaging equipment can steplessly adjust pouch length without changing the mold. Functions such as longitudinal sealing, transverse sealing, filling, embossing, dotted line cutting, and transverse cutting can be adjusted through man-machine interface.
6. It is accurate in measurement. Regarding fine granular materials, the sugar, oral saline and granule packing machine is designed with swing-out feeding pipes, which match with triangular adjustable feeding cups. Measurement can be adjusted independently with high precision, and each line's dosage can be adjusted easily and accurately.

7. The packaging equipment uses a photoelectric tracking system to ensure correct printing and has an automatic counting function.

8. With wide adaptability to the package film, the sugar, oral saline and granule packing machine provides automatic control of the sealing temperature and has high control accuracy ($\pm 1\text{C}^\circ$). It is suitable for the most complex packing film at home and abroad, such as PET/AL/PE, PET/PE, NY/AL/PE, NY/PE and so on.

9. Extra functions can be set up. For example, for sachet cutting, dotted line knife, flat cutting knife, and abnormal shape knife etc. are optional, in addition to various alarm requirements that can be chosen.

Main Technological Parameters:

Items / Model	DXDO-K900E
Pouch length	50~150mm (adjustable)
Pouch width	50~105mm (if you change width, please change bag mold)
Packing speed	20~40times/nim (depending on pouch size and material)
Filling capacity	5~100ml
Applicable film	PET/AL/PE, PET/PE, NY/AL/PE, NY/PE
Max. film width	900mm
Max. film diameter	$\Phi 300\text{mm}$ (as per customer's request)
Film core diameter	$\Phi 75\text{mm}$ (as per customer's request)
Electric source	380V 50Hz (as per customer's request)
Total power	12 kw
G.W.	1500kg
Package size	1650x1500x2200mm (LxWxH)