

Steam Tunnel SS Series



Product Range

- High Speed Shrink Sleeve Applicator
- Super Speed Shrink Sleeve Applicator
- Standard Shrink Sleeve Applicator
- Auto Cap Banding Applicator
- Economical Shrink Sleeve Applicator
- Steam Shrink Tunnel
- Electric Shrink Tunnel

Features

- All SUS304 stainless steel frame, elegant and compact, non-coating process, pollution free.
- Equipped with large size stainless steel steam storage tank, which stores enough steam to provide stable and even steam spray, and this helps shrinking effect more perfect.
- Dual wall design for energy saving, heat isolation and operator protection.
- Multiple sets of steam nozzle enable user to adjust according to sleeve position.
- Equipped with trapping and draining device for evacuation of waste steam.
- Equipped with Japanese steam pressure reducer to stabilize steam pressure.
- Extra steam exhaust design is able to prevent steam leaking from tunnel.

Specification

Model	SS - 1500	SS - 2000	SS-3000
Dimension (L x W x H)	1500 x 540 x 1850 mm	2000 x 540 x 1850 mm	3000 x 540 x 1850 mm
Weight	310 kg	400 kg	530 kg
Electric Power	AC 3 φ 220V; 750W		
Steam Input Pressure	Below 3kg		
Steam Nozzle	12 set	24 set	24 set
Steam Consumption	300 kg/h	330 kg/h	400 kg/h