



## ***Automatic Form Fill Seal Machine BP-1006***



- Automatic FFS Machine performs integrated operations from measuring, Bag making, filling & Cutting to Packaging.
- Powder Filling Machine equipped with a photocell apparatus for Powder Filling, Powder Packing, Masala Packing, Chips, Granules, Tablets, Pan Masala, Tobacco and its bye products, Candy, Jaljeera Powder, Detergent Powder, Lerron Powder, Fish Powder, Bettlenut, Concentrates, Tea, Coffee, Disposable Syringes, Pharmaceuticals etc.

### **Solid Automatic Packaging Machine for Powder & Masala Packing**

- Performs all intergrated operations of form fill seal machines from measuring, bag making, filling, sealing and cutting to packaging.
- Powder Packing Machine specially designed with Micro Adjustment for Packing Blended Tea, ORS Powder and Spices.

### **Automatic Quantitation Paste / Liquid Filling & Packaging Machine**

- Automatic packaging machine perform integrated operations from measuring, Bag making, Powder Filling and Packing.
- Equipped with a photocell apparatus suitable to pack Liquid, Paste, Jam, Honey Tomato Ketchup, Shampoo, Soya Milk etc.

### **Solid Automatic Packaging Machine**

- Performs intergrated operations from measuring, bag making, filling, sealing & cutting to packaging

•Equipped with a photocell apparatus suitable to pack General confectionaries, Chocolates, Cracker & other rectangular & square shaped solids

## TECHNICAL SPECIFICATIONS

Sealing Type	3 Side Sealing / 4 Side Sealing / Centre Sealing (On request)
Packaging Size	<b>L:</b> 40-120 mm or 100-240 mm (Pouch Length)
	<b>W:</b> 20-160 mm or 20-220 mm (Film Width)
	<b>(Enlarged type can be made on order)</b>
Packaging range	3-5 gm, 5-30 gm, 30-50 gm, 50-100 gm, 100-250 gm, 250-500 gm (Depending on Specific Gravity of Material to be packed)
Packing Material	Any heat sealable laminated film such as Polyester / Poly Paper / Polly Glassine / Poly Polyester / Met / Foil / Poly BOPP / Foil / Poly etc.
Speed	30-120 Bag (Depending on Flow Rate of the material to be packed)
Motor	1/2 H.P., 220 V / Single Phase / 50 Hz
Heater Load	3 Side Sealing / Centre Sealing (150 W x 2 Nos., 300W x 2 Nos.)
	4 Side Sealing (300 W x 4 Nos.)
Machine Dimensions	750 x 560 x 1750 (mm) (L x W x H)
Net Weight	380 Kilograms (appx.)
<b>Optional</b>	Coding Device
	Belt Conveyor
	Batch Cutting Device
	Bucket Elevator
	Nitrogen Flushing Arrangement
	Level Sensor Device
	Ultra Violet System
	Static Charge Eliminator
	Servo Stabilizer