

ZHV-120-III Automatic Cartoner Machine



Is suitable for ALU-PVC blister, ALU-ALU blister and similar product.

<u>Automatic cartoner machine</u> is new model developing base on integrated domestic and foreign advance technology. It is high technology product incorporates pneumatic-photo-electro-mechanic which improves by a large on performance of equipment and working efficiency, realize encasing fast, keep running steady and reliable when fast running.

<u>Automatic cartoner machine</u> is suitable for automatic feeding product of multi-variety multispecifications blister into carton. Adjust automatic feeding structure conveniently, setup quantity of blisters on touch screen randomly. On line product feeding and detecting, leaflet fold (1-4 folds) and feeding, leaflet detecting, canton opening and forming, products and leaflet pushing into carton, printing batch number, sealing carton with tuck-in or hot melt glue. Automatically reject lacking of leaflet or product and finished product out.

Features:

- International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- Adopt human-machine operation system.
- Automatically stop when machine is overload.
- Automatically reject lacking of package product and leaflet.
- Automatically display trouble, Alarm and count finished products. Stable performance, operation is easy.

JDZ-120 III(立式Vertical)

Main technical parameters

Encasing speed		30-120 (Cartons/min)
Carton	Quality requirement	250-350g/m ² Base on carton size
	Dimension range (L \times W \times H)	(65-125)mm × (30-85)mm × (12-50)mm
Leaflet	Quality requirement	60-70g/m ²
	Unfolded leaflet specification	(80-250)mm × (90-170)mm
	Fold range	【1-4】折(Fold)
Compressed air	Working pressure	≥0.6Mpa
	Air consumption	120-160L/min
Power supply		220V 50Hz
Motor power		0.75kw
Machine dimension (L \times W \times H)		2150mm × 1140mm × 1800mm
Machine weight		约1100kg