

**HORIZONTAL FLOW WRAPPER**  
**Model# Flow Wrap – 5S-3S**



**Flow Wrap – 5S**

- **Laminated Film - 3 – 5 mil thickness range**
- Advanced PLC Control System with User Friendly Color Touchscreen,
  - Easily Set and Change Packing Parameters
  - Display Production Data and Self-Diagnostics
- Servo Motor Drive System, Film Speed Automatically Synchronized with Conveyor Speed
- End Seal Jaw Speed Easily Adjustable by a Hand Wheel When Changing Bag Length
- Designed for Easy Maintenance and Cleaning
- Pulling Wheels Open by Means of Pneumatic Switches.
- The Sealing Wheels Open Automatically at Every Machine Stop
- Safety Guards Comply with CE Standard

Available Options: Photoeye for print registration  
Date Code Printer  
Line Shaft for Automatic Feeders

<b>MODEL # 5S</b>	<b>5S</b>
<b>Speed</b>	<b>Up to 250 pcs. per minute</b>
<b>Laminated Film Reel Width - Max.</b>	<b>19.7"</b>
<b>External Laminated Film Reel Diameter</b>	<b>13.8"</b>
<b>Max. Package Height</b>	<b>3.94"</b>
<b>Max. Package Width</b>	<b>7.87"</b>
<b>Min. Package Length</b>	<b>3.0"</b>
<b>Max. Package Length</b>	<b>22.2"</b>
<b>Compressed Air</b>	<b>87 psi</b>
<b>Supply Voltage</b>	<b>380 – 400 vac. / 3 phase</b>
<b>Power Consumption</b>	<b>3.0kw</b>