

15 Workstation Automatic Rotary Opp Hot Melt Labeling Machine



Opp labeling machine, or hot melt opp labeling machine is suitable for labeling opp material labels, on different volume and shape of bottles. No matter the bottle is round, square, or special shape, our machine is able to label it. It is easy to operate and convenient to change the mould. It's cable to work with PET blwoing machine, filling machine, code printung machine, water treatment, ect. In addition, the label cost is comparatively lower, it can meet the requirements of those users who have diverse kinds of the containers.

Feature

1. Auto cutting and Sticking circle or half circle of bottle. Auto melting and attaching glue on top and rear of the label, glue auto recycling.
2. Variable speed control system, synchronous automatic detection system, automatic adjust production speed, Always make the labeling machine at best production speed
3. Star Wheel separation and feeding ,correlation design transmission mode high-speed labeling, stable precision.
4. Servo motor synchronous tracking, with special designed vacuum drum adsorption, labeling precise and stable
5. Abnormal situation, this machine has safety device, automatic stop immediately.
6. Following conditions the machine will automatically stop and alarm:
 - 1) Label is not labeled on bottles
 - Label sticker failure
 - Label is about to run out
 - Abnormal bottle feeding
 - 2) Abnormal bottle out
 - 3) Abnormal bottle jam
7. The whole machine centralized lubrication system, easy to clean, lubrication and maintenance.

8. Techmach electronic automatic rectify guide system, digital electronic eye for ultrasound method. Non-contact electric eye, automatically adjust the label location. (optional).
9. Label top and end difference within 2mm (without Techmach), 1mm (with techmach)

Technical Parameter:

Item	Parameter data
Power supply	Three-phase 380V 50 Hz 8000W
The total length of equipment	3000mm (conveyor length 3000mm or can be regulate base on your product lines)
Equipment width	2500mm
Conveyor speed	30m/min (the speed of the transmission lines can be adjusted according to actual production)
The method of speed adjustment	uninterrupted - adjust rate
The largest Speed of labels feed	maximum speed of 100 meters labels / min
The largest speed of labeling	12000 PCS/H
Labeling accuracy	± 1mm
Integrated Labeling accuracy	± 1mm
Product Size	500ml
Maximum label width	150mm
The maximum length of label	500mm
The maximum diameter of label	600mm
Paper core diameter	152 mm
Labeling glue	leading and trailing edge gluing with hot melt
Gluing temperature	120~160°C
Type of label	opp label, paper-plastic composite film label, paper label
Labeling workstation	12 per cycle
The quantity of labeling mold	one suit (to be satisfied with one product, each mold contains infeed worm infeed starwheel, discharge starwheel, position bottle and so on)
Machine weight	about 3000 Kg