

GGS-240(P15) High Speed Plastic Ampoule Filling And Sealing Machine



The machine is suitable for liquid, medicine, beverage, health product, food, perfume, pesticide, cosmetics, electronic cigarette oil, dairy product, fruit pulp, oil and etc.

Introduction:

- 1. High capacity, high speed, high precision, and advanced motion controller. Steeples frequency conversion speed regulation control. Servo motor control
- 2. Human-machine interface, Servo film traction, the replacement of the mound and its length adjustment is convenient and easy to operate.
- 3. Automatic unwinding, roll film cutting and folding, it has positive and negative pattern alignment function with photoelectric device. As the bottom of the bottle is flat, it can stand. The product is exquisite and beautiful.
- 4. The use ratio of the packing material is as high as 95%-99%, which has small consumption. The packing cost is not restricted by the product shape, which helps to save cost.
- 5. It adopts electronic peristaltic pump device, which has convenient adjustment and simple cleaning.
- 6. High filling accuracy with suction back function without any dripping
- 7. The parts contacting with the medicine adopt high quality stainless steel 316L, and the outer cover of the machine is made of SUS304 stainless steel, which meets with GMP standard.

Specifications:

Max. forming depth	12mm
Capacity	22000 pcs/hour
Packing material	PET/PE, PVC/P, PVE/EVOH
Filling volume	1-100ml
Total power supply power	22KW
Voltage	380V/50Hz
Machine weight	3000Kg
Overall dimension (L*W*H)	7300×1050×1800(mm)
	Front: 2800×1050×1250(mm)
	Back: 4500×1050×1800(mm)