



Professional Auto Shrink Sleeve Label Machine



Automatic Shrink Sleeve Applicator is suitable for label sleeving in the fields of drinking, health-care products, cosmetics, washing articles for use, pharmaceuticals and petroleum and so on. Sunswell Series Shrinking Label Sleeving Machines are easy to control, to change bottles and labels smoothly, and easy for cleaning and maintenance. This series machines also have a high degree of automation.

Application:

Industries: fruit juice, tea drinks, dairy products, mineral water, purified water, sports drinks, condiments, sugar and wine, pharmaceuticals, cosmetics, washing supplies and other food and beverage industries and daily necessities industries;

Bottle type: round bottle, square bottle, flat bottle, curved bottle, special-shaped bottle, cup, bucket, pot, etc.

Features:

- 304 stainless steel main frame: waterproof and rust-proof, stable structure;
- Free replacement and debugging tool holder, rotary cutting cutter head: long life, convenient and fast tool change, smooth and beautiful cut surface;
- Stand-alone synchronously driven six-point positioning center guide column: stable, accurate and smooth label guide;

- Tail-shaped label controls the electric eye frame: the position of the sub-label is convenient to adjust, and the film material cutting accuracy is higher;
- Synchronous bottle separator: The bottle is conveyed smoothly and evenly, ensuring efficient and stable work for a long time;
- Stand-alone synchronous drive brushing: precise target shooting, no bias, no flying target;
- Bottle detection, label control electric eye: imported high-precision photoelectric sensors, accurate label segmentation, no blocking, and no leakage;
- Fully automatic heat shrinkable film sleeve labeling machine can be equipped with independent feeders and freely positioned feeders;

Technical parameters:

- Input power: 2KW;
- Input voltage: 220VAC;
- Production efficiency: 50-150 bottles / min;
- Applicable bottle diameter: $\Phi 28\text{mm}-\Phi 125\text{mm}$;
- Applicable label length: 30mm-250mm;
- Applicable label thickness: 0.03mm-0.13mm.