

## ***Automatic Paste Type Filling Machine – 2 Nozzle – CE-1000L/GCGA-2***



This machine is applied for viscosity and paste filling similar like juice, milk, yogurt, cream, shampoo, liquid soap, lubricant, engine oil products. It is able to integrate to capping machine and labelling machine in bottling line, fully complete and intelligence control advantage.

### **Characteristic:**

- Adopt volumetric piston pump, pneumatic control ss check valve to filling various kinds of liquid from light to medium heavy.
- Pneumatic control piston pump, easy adjust filling volume.
- Auto shut on/off filling nozzle, prevent drop while filling.
- Automatic tray collector under filling nozzle, to avoid dropping on bottle.
- Convenient to take out component parts to clean and sterilize, adjust to fit to other bottle size with no change parts.
- Frequency speed control, no bottle no fill intelligence.
- Whole machine designed and manufactured accordance to GMP regulation.

### **Application Range:**

Type: massage oil, antifreeze, hydraulic oil, painting, laundry detergent, liquid detergent, liquid fertilizer.

**Technical Parameter:**

<b>Model</b>	<b>CE-1000L/GCGA-2</b>	<b>CE-1000L/GCGA-4</b>	<b>CE-1000L/GCGA-6</b>
<b>Brand</b>	FULLWELL	FULLWELL	FULLWELL
<b>Filling volume</b>	50-1000ml	50-1000ml	50-1000ml
<b>Filling type</b>	Piston quantitative filling	Piston quantitative filling	Piston quantitative filling
<b>Speed</b>	300-600b/h	600-1000b/h	1200-1500b/h
<b>Filling accuracy</b>	± 1%	± 1%	± 1%
<b>Material</b>	Stainless steel 304	Stainless steel 304	Stainless steel 304
<b>Air pressure</b>	0.5-0.8Mpa	0.5-0.8Mpa	0.5-0.8Mpa
<b>Power</b>	220v, 50Hz, 500w	220v, 50Hz, 500w	220v, 50Hz, 500w
<b>Air consumption</b>	200-300L/min	200-300L/min	200-300L/min
<b>Weight</b>	400kg	550kg	700kg