



XT-2520 High speed round bottles labeling machine



1. Applicable to label a whole curved surface or half curved surface on rotundities from medicine, food, agrochemical and other light industries, it can be used solely or connect with assembly line.
2. The running of complete machine is stable and at high speed with the use of imported servo control system.
3. Amiable and advanced touch human-computer interfaces which is easy and intuitionist to operate and has complete functions including abundant online help;
4. The using of world famous accessories ensures the stability and reliability of the machine running;
5. Using of special bottle-distributing mechanism to avoid the materials being scratched and with which the machine can be adjusted and located quickly to label bottles with any diameter without replacing accessories;
6. Automatic synchronous tracking to conveying, closing of the idler wheel and labeling speed makes it easy and fast to adjust;
7. Automatic sensory test functions, such as cancelling labeling without objects there, stopping running or raising an alarm without labels to use to avoid omitting or wasting labels.

Technical parameters

Model / technical parameters	XT-2520
Labeling speed (pcs/min)	40-200 (relate to material and label size)
Labeling accuracy (mm)	±1.0mm (material and label sizes are not counted in)
Label size (mm)	(L) 20-280mm (H) 10-140mm
Material size (mm)	Φ20-φ100mm (H) 40-200mm
Roll inside (mm)	φ76mm
Roll outer side diameter (mm)	(Max)Φ350mm
Machine size (mm)	(L) 2000* (W) 900* (H) 1500(mm)
Power supply	AC220V 50Hz/60Hz 1200W