

Pillow packing machine JR-250B/250D



Features:

 \star Dual frequency conversion control, bag length can be set and cut on one step, saving time and film.

 \star Interface features easy and quick setting and operation.

★Self failure diagnosis, clear failure display.

 \star High sensitivity photoelectric eye color tracing. Numerical input of cutting seating position for extra accuracy.

★Temperature independent PID control, more suitable for packing different materials.

★Positioned stop function, without sticking knife of wasting film.

★Simple driving system, reliable working, convenient maintenance.

★All control is realized through software, easy for function adjusting and technical upgrade.

Application:

Packing various kinds of regular objects like biscuits, pies, chocolates, bread, instant noodles, moon cakes, drugs daily appliances, industrial parts, paper boxes, plates, etc.

Technical parameters:

Model	JR250B	JR250D
Bag length	MAX. 250mm	
Bag length	65-90mm or 120-280mm	90mm-220mm
Product height	30 -110 mm	
Film width	MAX. 40mm	MAX. 55mm
Film roll diameter	MAX.320mm	
Packing Speed	40-230(bags)/(min)	
Power Supply Specification	220V50/60H22.6KW	
Overall Size	(1) 3770 *(W) 670* (H) 1450mm	
Dead Weight Of Machine	800Kg	