

SPC-350B/450B Model Label Sleeving Machine



It adopts the imported color touch screen.

The machine can operate at the same limited velocity and there is no bottle overturning or label missing.

It has super powerful servo electrical appliance configuration, motor encoder for servo motor conveying line with high disposition, automatic trace with electric eye and whole line automatic stepless speed adjustment.

The mechanism is a kind of new-type & advanced driving device of hot shrink trapping label machine, that is, a kind of device with four-wheel drive, automatic centering and four-wheel balanced pressure, which has achieved the goals of smooth, stable and swift label transmission.

Electrical Configuration

The electrical appliance adopted by this type of label sleeving machine are all imported configuration, in addition, it adopts the high-velocity positioning module, imported servo motor, servo driver, servo controller and fully-automatic adjustment as well as humanized operation.

Applicable Types of Bottles

The velocity of this type machine reaches within 350-450 Bottles per minute; it applies to such food & beverage industries as fruit juice, tea drink, dairy products, pure water, condiments, beer and sports drink, etc. of all kinds of bottle types. It not only has a highly precise position for casting label, but also can withstand the perfect shape of the bottle after shrinkage.

Model	SPC-350B	SPC-450B
Input Power	3.0KW	6.0KW
Input Voltage	φ3380/220VAC	φ3380/220VAC
Production Efficiency	350(Bottle/min)	450(Bottle/min)
Size of Host Machine	L2100mm×W1100mm×H2000mm	L2500mm×W1200mm×H2000mm
Applicable Diameter of Bottle Body	Φ28mm-Φ125mm	Φ28mm-Φ125mm
Applicable Length of Label	30mm-250mm	30mm-250mm
Applicable Thickness of Label	0.35mm-0.13mm	0.35mm-0.13mm
Applicable Internal Diameter of Paper Tube	5" -10" Free Adjustment	5" -10" Free Adjustment