

Double Twist Candy Packing Machine (F-S800)



Double twist packing mainly applied for milk candy, peanut candy, chocolate, etc. The feeding plate has the connector to install auto hopper device.

Main Features

1. High-density cam indexing unit, cam gear transmission.
2. Automatic bag length adjustment, Double layer films available.
3. Equipped with Automatic photocell avoiding film-cutting error.
4. The connected part with food is stainless steel structure, no pollution, high-level food hygiene.
5. Frequency converter, stepless speed regulation.

Optional accessories & special versions

- Stainless steel frame
- Date coder
- Auto vibration device

Purpose and features:

The machine is suitable for single grain kink of candy, beef etc packing, high production efficiency, product packaging after forming the beauty is generous, package form is the pursuit of the best choice of the product standardization of food manufacturers. The built-in sugar tray feeding device enables the production to achieve high speed, greatly improving the production efficiency while saving manpower, thus reducing the production cost for the production unit. The double layer transport device of packaging film can be packed in a single layer or double layer. Synchronous control of paper removal without sugar, no empty bags, leakage bags, ensure 100% packaging rate. Variable frequency speed control, so that the production of products more idealistic.

Specifications:

Packing speed	50-600 grain/minute
Net weight	1080KG
The product specification	length12-34*width10-28*height6-20mm
Outside dimensions	1950mm×1090mm×1475mm(L*W*H)
Total power	2.5KW
Voltage	380V, 50HZ
The packing shape of the product	round slice\spherical\ellipse, waist round, cylindrical, rectangular square etc
Adopted product	milk candy, chocolate beans, toffee, peanut candy, beef granule
Film	OPP, CPP, PET. Aluminum plating Film, hot or cold sealing packing film, etc