

Small Tea Bag Packing Machine XY-70BT



Introduction for tea bag packing machine:

1. This machine adopts correcting system controlled by microcomputer, owing to a response signal is handle and pass through microcomputer it can accomplish whole set to synchronization, sack length, position fixing, voluntarily follow the tracks of light-mark and voluntarily diagnose trouble and show to screen.
2. This machine can automatically complete a series of actions, such as bag making, the measuring, filling, inflating, counting, sealing, code printing, material giving, stopping in certain quantity, fixed-bag cutting and same cutting.
3. Suitable for tea like green tea, black tea, herbal tea, flower tea etc. and the fluidity granule, particle material (sugar puffed, fried fresh chip, cracknel, bean and so on).
4. Packing material should have hot-sealing material, such as polyester/polyethylene, nylon-compound membrane, strengthen-compound membrane, BOPP and so on

Feature:

1. Measuring cup or electronic scale (2 heads or 4 heads) for your options, filling material in high accuracy.
2. All the contact part of the packing machine is made from SS304, clean and safe, easy for cleaning.
3. PLC touch screen and important electric components are imported overseas.
4. The processes of bag making, measuring, filling, sealing, cutting, counting and heat pressing codes can be done automatically.
5. Our machine can make 3/4-pillow bag and connected bag. We can add make round hole or butterfly hole in bag.
6. The corner of the bag can be round through using the punch mold.
7. Low noise, stable system, simple operation.
8. Double heating tubes, the temperature more average, to make more perfect bag.
9. This model got higher speed, technology very mature, the continuous running make it very high efficiency.
10. Pneumatic driven type, combined with the air compressor, then power on to run machine, easy operation.

Technical data:

| Model | XY-70BT |
|--------------------|------------------------------------|
| Power | AC220V 50/60Hz 1.90KW |
| Bag size | 30-200mm(L) |
| | 30-140mm(W) |
| | Film width Max. 300mm |
| Bag type | Three/four/pillow side sealing bag |
| Measure range | 1-15g |
| Film roll diameter | Max. 320mm |
| Packaging speed | 20-50bag/min |
| Machine weight | 400kg |
| Machine size | 1500*700*1700mm (LxWxH) |