SCIENCE

High Speed Automatic Bag Packing Machine



Applicable for packing various solid regular objects, such as biscuits, bread, instant noodle, ice cream, moon cake, candy, medicine, commodity, hardware or loaded by box/tray...etc.

Main Features:

- 1. English (or specificity language) display (the translation will be finished by your side);
- 2. Germany Siemens / Taiwan Weinview touch screen clearly shows the various working conditions, operating instructions. The operation is simple and intuitive;
- 3. Germany Siemens/Japan Mitsubishi/ Taiwan Airtac PLC provides stable working procedures;
- 4. The formula of 10 products can be preset to adapt to the packaging of quick replacement products;
- 5. Using intelligent temperature controller, the temperature difference can be controlled within 2 degrees:
- 6. The sealing and cutting position on the touch screen can be setting when machine non-stop;
- 7. With the horizontal tooth-shaped sealing, the packaging is more firm;
- 8. CE installation standards can be adopted, the electrical box protection standard can reach IP65; the shape of all kinds of punching can be designed based on your requirements;
- 9. The machine is suitable for different bag types, such as: back seal, four-side seal, three-dimensional bag, handbag, punching bag;
- 10. High-sensitivity electric eye automatic positioning tracker, no manual adjustment after setting, sealing and cutting size, accurate position, sealing with good appearance;
- 11. Automatic counting the production, output is accurate and clear view in the touch screen;

Technical Parameters:

Finished package size	ı	30~500mm
	\	
	W	30~110mm
	Н	5∼40mm
Sealing strength		>15N/mm²
Capacity		5~230Bags/min
Max. film width		350mm
Power supply		220V 50/60Hz 2.4KVA
New weight		900kg
Overall size		3780×830×1560mm