

Liquid Automatic Packing Machine LQ-V-1L



Feature

- The length of products can be adjusted from 100 to 200m/m and the width adjustment requires replacement of the former.
- It is a machine that is universally selected as 3-side vertical packaging machine for its outstanding convenience and reliability based on stabilized mechanic design.
- Anyone can operate this machine with ease and the assembly/disassembly can be done conveniently in a single touch.
- Adjusting films left and right and calibrating the I-Mark can be done in front of the machine. A flashing light is turned on 2 minutes before the film is finished. When the films are completely consumed, the machine will stop at its designated position.

Contents

Red pepper paste, soy bean paste, ssamjang (seasoned paste for wrap cabbages), aqueous bonding agent, and other relevant products of high viscosity

Packing material

AL+PE, OPP+PE, NY+PE, Other relevant packing papers with 3 sides sealed available for thermal sealing

Specification

Packing row	1 Row (production option)
Capacity	10~30 EA/min (on 1 row)
Date printer	Jet Printer & Others Date Printer Option
Packing size	W : 200~350 × L : 350~500mm (option feature)
Filling capacity	200g~5kg(option feature)
Power consumption	Domestic : 220/380V×60Hz - AIR 5 ~ 7 Kw/h
	Overseas : 220/380/440/50×60Hz - AIR 5 ~ 7 Kw/h