



Flow Pack Wrapper MK-350



Flow Pack Wrapper, MK-350B



Flow Pack Wrapper, MK-350B

Mingke Pack offers two flow pack models: the MK-350B and MK-350X. Both feature a maximum bag width of 350mm. The difference lies in the film roll position, located in the top and bottom of the transverse sealing jaw.

The MK-350B flow pack wrapper's film reel is located over the transverse sealing jaw to manage regular products, like bread, chocolate, and more.

The MK-350X flow pack wrapper uses a bottom film feeding mode, making it applicable for packaging loose materials, including disposable tableware, cotton swabs, hardware fittings and more.

Bag materials:

OPP/PP composite film, OPP/CE composite film, MST/PE composite film, PET/PE composite film, aluminum foil.

Additional Options:

- Ink Printer.

Technical Parameters:

Model	MK-350B	MK-350X
Packing speed	40-230bag/min	40-230bag/min
Bag size	L:65-190mm or 120-280mm, W:50-160mm	L:65-190mm or 120-280m, W:50-160mm
Max film width	350mm	350mm
Product Height	Max.40mm	Max.40mm
Film Roll Diameter	Max.320mm	Max.320mm
Power source	220V,50/60HZ,2.6Kw	220V,50/60HZ,2.4Kw
Weight	550kg	550kg
Overall size	(L)3770×(W)720×(H)1450mm	(L)3770×(W)720×(H)1450mm