



## *Link-50I Automatic Sealing Carton Machine*



Link – 50 automatic folding & sealing machine on both sides of the belt drive, I use the stick tape sealing, automatic folding lid sealing up and down, fast, stable, and sealing effect level, standard, beautiful, can according to the carton specifications, automatically adjust the width and height, simple, quick, convenient, and can replace manual, improve the efficiency of up to 80% of production, save 5-10% consumables, is the enterprise It is a good choice to save cost, improve production efficiency and realize packaging standardization. This automatic folding and sealing machine is also known as adaptive automatic sealing machine, automatic adjustment according to the size of the carton, if you need to manually adjust the size of the carton, it is recommended to use manual folding and sealing machine (manual adjustment).

### **Sealing machine equipment characteristics:**

- Manufactured with international advanced technology and imported parts and electrical components;
- Can be equipped with different brands of automatic baler use;
- The height of standard machine surface is 600mm/650mm;
- Automatic adjustment of width and height when changing carton specifications;
- Automatic folding cover, up and down sealing completed at one time, suitable for the use of a variety of specifications of carton at the same time;
- Equipped with blade protection device. Avoid accidental stab injury during operation;
- It can be combined with Link-50H corner sealing machine to complete i-shaped sealing.
- It can be operated independently or used in conjunction with automatic packaging assembly line, which is the choice for enterprises to save costs, improve production efficiency and realize packaging standardization.

### Application scope of sealing machine:

Relying on the advantages of the above automatic folding and sealing machine is widely used in food, medicine, beverage, tobacco, daily chemical, hardware, toys, electronics and other industries at home and abroad.

### Technical Parameters:

Model	Link-50I
Applicable to the power supply	380V/50Hz / 0.4KW
Work pressure	5-6 kg /cm <sup>2</sup> 100 nl/ min
Minimum packing size	L 280 * W 120 * H 150mm
Maximum packing size	L 600 * W 500 * H 500mm
Mesa height	H 600mm-650mm
The belt speed	28 m / min (12-17 kes / min)
Packing tape	BOPP/PVC
Tape size	W48, 60, 75mm
Installation dimensions	L 1700 * W 920 * 1450mm
The net weight	280Kg