

## ***WP-T Series Quad Seal Packing Machine***



### **Application**

- ◎ Applicable bag type: quad seal bag, gusset bag, pillow bag.
- ◎ Applicable film materials: a variety of laminated film, film thickness range is 0.05~0.15mm.
- ◎ Applicable packing materials: a variety of snack food, chemical raw materials, herbal, small hardware, such as candy, bean, pet food, dry fruits, sugar, spice and some others granule product, also some powder like milk powder, coffee powder, etc.

### **Feature**

- ◎ Facing the high-end market, a more beautiful stand up bag type is needed to enhance product image.
- ◎ Bag length is controlled by eye mark tracking device or parameter setting(encoder is an option). Date print position can be adjusted too.
- ◎ Automatic making bagging, quad sealing, heat sealing, date printing, hole punching(as an option), etc.
- ◎ Panasonic PLC control, 9.7" touch screen, easy to operate and maintain.
- ◎ Operating easily, low maintenance cost, also can work with different type weigher.
- ◎ Three-speed-control mode for roll film feeding.
- ◎ Safety door protection, with door open alarm and machine stops, no film alarm, no ribbon alarm function and so on.
- ◎ Machine is made by stainless steel 304.

## Technical Parameters

Model	HT5235	ET5235
Film Width	240-520mm	240-520mm
Sealing width	4-8mm	4-8mm
Front surface width	60-190mm	60-190mm
Side surface width	40-100mm	40-100mm
Bag Length	150mm-350mm	150mm-350mm
Packing Speed	45 (包 bags/min)	45 (包 bags/min)
Film pulling driven system	servo motor	servo motor
Horizontal sealing driven system	servo motor	cylinder
Voltage	6KW/220V/50(60)HZ	5KW/220V/50(60)HZ
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.3m³/min	0.7m³/min
Machine Size(mm)	2020*1440*2130	2020*1440*2130
Machine Weight	780KG	750KG

Model	HT6240	ET6240
Film Width	270-620mm	270-620mm
Sealing width	4-8mm	4-8mm
Front surface width	70-220mm	70-220mm
Side surface width	45-120mm	45-120mm
Bag Length	180mm-400mm	180mm-400mm
Packing Speed	45 (包 bags/min)	45 (包 bags/min)
Film pulling driven system	servo motor	servo motor
Horizontal sealing driven system	servo motor	cylinder
Voltage	7.3KW/220V/50(60)HZ	5.8KW/220V/50(60)HZ
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.3m³/min	0.9m³/min
Machine Size(mm)	2330*1520*2025	2330*1520*2025
Machine Weight	880KG	850KG