

DPH-260K High Speed Blister Packaging Machine



This machine is suitable for pharmaceutical, food, health care products, cosmetics and other industries. It can seal blister packaging of various specifications of tablets (sugar-coated tablets, plain tablets), various capsules, various candies, foods, electronic components and other special-shaped solid items.

Features

1. Adopt Taiwan Liming high-precision gear servo reducer, with large torque and increased service life.
2. Equipped with air pressure and water pressure controllers. When the pressure value is lower than the set value, the display screen will display the fault and alarm and stop.
3. The main station bearings are imported from Japan NSK brand.
4. Solenoid valves, vacuum valves, etc. are imported from Japan SMC brand.
5. The roller brush device has a dust suction function, which can effectively absorb the dust on the surface of the packaging material and improve the heat sealing effect.
6. Using screw servo traction, the traction stroke precision dimension is more accurate.

Specifications

Punch Speed:	20~40 times/min
Production Capacity:	250,000~500,000 capsules/hour
Optional range of feed stroke:	40-120 mm
Max Forming Area:	245~350×112mm
Maximum Forming Depth:	Alu/Alu12mm
Upper and lower forming heating power:	2KW (×2)
Heat Seal Heating Power:	1.5~2KW
Overall Dimensions:	4800×900×1740mm
Machine Packaging Size:	5500×970×1840mm
Weight:	3000~4000Kg
Motor Power:	1.5~2.5KW
Air Pump Volume Flow:	≥0.25m ³ /min
Heat-seal aluminum foil:	0.02×250mm
Medical PVC:	0.25 (0.15-0.5) ×250mm
Heat-seal aluminum foil:	0.02×250mm
Total Power:	3-phase 4 wire 380V 50HZ (220V 60HZ) 7.5~8.5KW