

PC-C Series Tablet Coater



With an ergonomic design, compact size, good performance and all the required functions, the PTK tablet coating machine model, PC-C series ideal for laboratory use. The PC-C series is equipped with changeable drum.

Specification						
Model	PC-C300 (Electric Heat Exchanger)			PC-C600		
Drum Diameter	350 mm	400 mm	450 mm	460 mm	635 mm	660 mm
Drum Opening Diameter	150 mm	180 mm	230 mm	230 mm	300 mm	300 mm
Drum Working Volume	0.8 - 2.2 l	2 - 4.5 l	4 - 5.5 l	4.5 - 8 l	8 - 15 l	15 - 30 l
Output Capacity *	0.6 - 1.5 kg	1.4 - 3.2 kg	2.8 - 3.9 kg	3.2 - 5.6 kg	5.6 - 10.5 kg	10.5 - 21 kg
Spray Gun	1 ea			1 or 2 ea		
Drive Power	0.4 kw			0.75 kw		
Machine Weight	900 kg			500 kg	600 kg	650 kg
Cabinet Weight	250 kg			250 kg		
Machine Dimension	1,000 * 1,300 * 1,848 mm			998 * 1,181 * 1,353 mm		
Cabinet Dimension	800 * 550 * 1,160 mm			800 * 550 * 1,160 mm		
Power Supply Data	220/380 Vac 3Ph 50/60 Hz					
Control Power	24 Vdc					

Layout Drawing

- 1. Main Machine
- 2. Heat Exchanger
- 3. Dust Collector

- 4. Liquid Tank
- 5. Control Cabinet
- 6. Drum Changer (option)

- 7. HEPA Filter (option)
- 8. WIP Rack (option)
- 9. Auto Damper (option)

