

SLM 150 Automatic Sleeve Labeling Machine



Function:

- All-Cover type stainless steel host machine: The whole machine is waterproof as well as rustless.
- Adjustable cutter head: Uniquely cyclotron cut-off, double sided cutting edge with a long service life.
- Single positioning centre uide pillar: A more stable label delivery.
- Synchronous bottle divider: A more stable transmission for bottle.
- Bottom set of label brush: A more precision for casting label.
- Label-Controlling electric-eye shelf: Unquie combination of tail and electric-eye to improve the precision for cutting off the membrance materials.
- Push-button control cabinet: A more humanized operation.
- Independ feeding material shelf: The position of the material shelf is optional at will.
- Electrical appliance Configuration Specification:
- It adopt PLC programmable controller, improved servo motor, servo driver, frequency converter and transducer; besides, it adopt the positioning module to ensure the casting label precise, rapid and stable.

Product Series:

Model	SLM150	SLM250	SLM250D	SLM300	SLM400
Power supply	3.0KW	3.3KW	6.0KW	6.0KW	6.0KW
Input voltage	220V/380V	220V/380V	220V/380V	220V/380V	220V/380V
Capacity	9000BPH	15000BPH	15000*2BPH	18000BPH	24000BPH
Host machine dimension	2100*850*2000	2100*850*2000	3200*1100*2070	2200*1100*2200	2500*1200*2200
Framwork material	Stainless steel				
Length of label(mm)	30-260	30-260	30-260	30-260	30-260
Thickness of label(mm)	0.03-0.13	0.03-0.13	0.03-0.13	0.03-0.13	0.03-0.13
Diameter of bottle	28-125	28-125	28-125	28-125	28-125
Height of bottle	50-280	50-280	50-280	50-280	50-280
Bottle shape	Round/Square/	Round/Square/	Round/Square/	Round/Square/	Round/Square/
	Flat/Oval	Flat/Oval	Flat/Oval	Flat/Oval	Flat/Oval