



Automatic Shrink Sleeve Applicator Machine



Product Description

- * Various bottle type; round, square and so on.
- * High precision location; save cost and correct.
- * Suitable for adjustment inside film range from 3 to 10.
- * Man-machine conversation liquid crystal screen; easy operation
- * PLC control system
- * High-speed sleeve film. (Temperature; from 100 to 600°C suitable for various film material)
- * Screw transportation located system; Location for various shape bottles.
- * No need tool adjustment

Features:

- 304 stainless steel main frame: waterproof and rust-proof, stable structure;
- Free replacement and debugging tool holder, rotary cutting cutter head: long life, convenient and fast tool change, smooth and beautiful cut surface;
- Stand-alone synchronously driven six-point positioning center guide column: stable, accurate and smooth label guide;
- Tail-shaped label controls the electric eye frame: the position of the sub-label is convenient to adjust, and the film material cutting accuracy is higher;
- Synchronous bottle separator: The bottle is conveyed smoothly and evenly, ensuring efficient and stable work for a long time;
- Stand-alone synchronous drive brushing: precise target shooting, no bias, no flying target;

- Bottle detection, label control electric eye: imported high-precision photoelectric sensors, accurate label segmentation, no blocking, and no leakage;
- Fully automatic heat shrinkable film sleeve labeling machine can be equipped with independent feeders and freely positioned feeders;

Technical parameters:

- Input power: 2KW;
- Input voltage: 220VAC;
- Production efficiency: 50-150 bottles / min;
- Applicable bottle diameter: Φ 28mm- Φ 125mm;
- Applicable label length: 30mm-250mm;
- Applicable label thickness: 0.03mm-0.13mm.