XT-2510 Automatic round bottles labeling machine

1. Applicable to label whole curved surfaces or half curved surfaces on rotundities from medicine, food, agrochemical and other industries;

2. Using well-known motor drive which ensures a stable and reliable label-feeding speed;

Advanced touch human-computer interface which is easy and intuitionist to operate and has complete functions including abundant online help;

3. Automatic sensor detection functions including cancelling labeling without objects there and stopping running or raising an alarm without labels to use to avoid omitting or wasting labels;

4. Rotary rolling depression body adopting elastic sponge-covered belt makes the labels more smooth, firm and with no wrinkles which enhances the packaging quality greatly;

5. Simple and compact machine construction makes it easy to operate and maintain;

6. You can also link the back part with assembly line or receiving platform which is convenient for collecting, tidying and packaging the finished products.

Tech Parameters

Model / technical parameters	XT-2510
Labeling speed （pcs/min）	40-150 pcs/min (relate to material and label size)
Labeling accuracy （mm）	±1.0mm (material and label sizes are not counted in)
Label size （mm）	（L）20-280mm （H）30-144mm
Material size （mm）	Φ20-φ100mm （H）40-200mm
Roll inside （mm）	φ76mm
Roll outer side diameter （mm）	(Max)Φ350mm
Machine size （mm）	（L）2000* （W）850* （H）1350(mm)