

Vegetable and Fruit Packing Machine TFD-CT250X/CT350X



- The key parts of machine are adopted of stainless steel, in accordance with food QS and medicine GMP health requirements.
- Servo motor control, packing goods faster, convenient with superior quality.
- High sensitive electronic eye tracing system, after setting, the machine is no need to adjust by hands, the cutting position is accuracy, and the seal is tight and beautiful.
- Temperature is controlled by PID intelligence independently and steadily which is more suitable to various packaging material.
- Color touch-screen display, machine can be turned off by position, fault is self-diagnosed, fault is display clearly.
- Counting automatically, packaging production's counting is accuracy.
- Machine's design and the convey system is simple, the work is more reliable which is more convenience to maintain.

Technical parameters:

Type	TFD-CT250X	TFD-CT350X
Width of film	≤ 250mm	≤ 350mm
Thickness of film	40-70um	40-70um
Dimension of film roll	OUTER DIAMETER $\Phi \leq 300$ mm, INNER DIAMETER $\leq \Phi 75$ mm	OUTER DIAMETER $\Phi \leq 300$ mm, INNER DIAMETER $\leq \Phi 75$ mm
Bag size	(55-240)*(30-100)*(3-40) mm (L*W*H)	(65-330)*(50-180)*(3-55) mm (L*W*H)
Speed	40-180 bags/min	40-200 bags/min
Power	220V,50HZ, 2.6KW	220V,50HZ, 2.6KW
Machine dimensions	3770 * 650 * 1450mm (L*W*H)	3770 * 720 * 1450mm (L*W*H)
Gross weight	400 kg	450 kg
Optional device	Printer, Gas Charging device, Feeder, Tidier	Printer, Gas Charging device, Feeder, Tidier