

Food Pillow Packing Machine AT-250/350/450/600



Double frequency converter controller, length of package will cut immediately once setting, adjustment needless, saving time and film.

Features:

- Compact structure, stable function and simple operation.
- Double frequency converter controller, length of package will cut immediately once setting, adjustment needless, saving time and film.
- It adopts imported electric appliance, touch man machine interface, convenient parameter setting.
- Self-checking function, trouble can be read easily. High sensor photoelectric color chart tracking, make the cutting position more correctly.
- Dependent temperature PID controlling suitable for various materials of packaging membrane. Position stop function, no adhesive and no waste of membrane.
- Clean rotation system, more reliable operation and more convenient maintenance.
- All the controlling operates by the software, convenience for function adjustment and technical upgrading.

Main Technical Data:

Type	AT-250	AT-350	AT-450	AT-600
Film width	250MM	350MM	450MM	590MM
Bag Length	65-330MM	65-330MM	110-350MM	150-400MM
Bag width	30-120mm	30-150MM	50-200MM	50-270MM
Products High	Max.45mm	Max.50mm	Max.80mm	Max.100mm
Packing speed	40-220bag/mins	40-220bag/min	40-180bag/min	50-120bag/min
Power	220V 50/60HZ 2.4KW	220V 50/60HZ 2.4KW	220V 50/60HZ 2.7KW	220V 50/60HZ 4.2KW
Machine size	4000x920x1500 MM	4100x1050x1560 MM	4100x1050x1560 MM	4200x1200x1750 MM
Machine Weight	500kg	600kg	680kg	780kg