



## *Link-50AS Automatic Top And Bottom Drive Belt Adhesive Taping Machine*



Link-50AS upper and lower sides of the carton sealing machine are driven by belts on the upper and lower sides of the carton sealing machine. It adopts sticky tape for sealing, and the upper and lower sealing is fast and stable. The sealing effect is smooth, standardized and beautiful. The width and height can be adjusted manually according to the carton specifications. , Simple, fast, convenient, can replace labor, improve production efficiency by up to 80%, save 510% of consumables, is a good choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization. The driving carton sealing machine is also called the upper and lower side driving carton sealing machine, which is manually adjusted according to the size of the carton.

### **Features of carton sealing machine:**

- Manufactured with international advanced technology, and selected imported parts and electrical components;
- The standard machine table height is 600mm;
- Manually adjust the width and height according to the carton specifications;
- Using the upper and lower sides of the belt drive is suitable for narrow and tall cartons;
- Equipped with blade guard. Avoid accidental stabbing during operation;
- Manually fold the upper cover, and seal the box with the upper and lower characters at one time;
- It can be operated on a stand-alone machine, or it can be used in conjunction with an automated packaging line. It is the choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization.

## Application range of sealing machine:

Relying on the above advantages, the upper and lower side drive case sealing machines are widely used in food, medicine, beverages, tobacco, daily chemicals, hardware, toys, electronics and other industries at home and abroad.

## Technical Parameters:

Model	Link-50AS
Applicable to the power supply	220V/50Hz / 0.4KW
Work pressure	5-6 kg /cm <sup>2</sup> 150 ml/ min
Minimum packing size	L 150 * W 120 * H 200mm
Maximum packing size	L Unlimited * W 400 * H 500mm
Mesa height	H 600mm-650mm
The belt speed	20 m/min
Packing tape	BOPP/PVC
Tape size	W48, 58, 72mm
Installation dimensions	L 1000 * W 880 * 1370mm
The net weight	120Kg