TINUTIU"

Air Suction Continuous Sealer FRMC-1010III



Product Details

- Horizontal nozzle vacuum band sealer
- Maximum loading for single bag can be only 1kg
- Outer housing: powder coating or stainless steel housing.
- Available for: foods, chemicals and hardware parts.
- Packing material: any kinds of heat sealable material.
- The printing wheel in the machine can be used for both R arrange and T arrange of types.
- Counting device is optional.
- Novel design idea and advanced manufacturing technology is adopted to make structure of machine more reasonable and perfect. Apart from functions of sealing and printing, model FRMC-1010III has function of air suction.

Parameters:

FRMC-1010III	FRMC-1010III
Voltage (V/Hz)	AC 220/50 110/60
Motor Power (W)	100
Suction Pump Power (W)	1200
Sealing Power (W)	400×2
Printing Heating Power (W)	40×2
Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10
Temperature Range (°C)	0-300

Printing Type	Solid-Ink Roller
Distance from Sealing Center to Conveyor Table (mm)	10-40
Distance from Base plate to Interior Conveyor (mm)	85-115
Conveyor Table Size (L × W) (mm)	1065×205
Overall Conveyor Loading (kg)	≤3
External Dimensions (L × W × H) (mm)	1065×550×960
Net Weight (kg)	74