

WP-EQ Series Shatterproof Packaging Machine



Application

- ◎ Applicable bag type: Pillow bag, Gusset bag, Seal type bag, Triangle bag.
- ◎ Applicable film materials: A variety of laminated films, single-layer PE film, film thickness range 0.04mm~0.15mm.
- ◎ Applicable packing materials: A variety of snack food, deep frozen food, milk powder, coffee, oatmeal, granulated sugar, salt, puffed food, rice, herbal, tea, small hardware etc

Feature

- ◎ PLC control, man machine interface, easy to operate and maintain.
- ◎ Equipped with servo motor and optical tracking devices to keep accuracy and high speed.
- ◎ Automatic multihead weighing and vertical packaging combine in one unit.

Technical Parameters

Model	WP-EQ5235	WP-EQ6240
Film Width	160 ~ 520mm	200 ~ 620mm
Bag Size	L*W=(40-350)*(70-250) mm	L*W=(40-400)*(90-300) mm
Packing Speed	60 bags/min	50 bags/min
Inclined angle	45°	45°
Horizontal sealing driven system	cylinder	cylinder
Film pulling driven system	cylinder	cylinder
Voltage	3.2KW/220V/50(60)HZ	3.5KW/220V/50(60)HZ
Gas Pressure	0.2 ~ 0.8MPa	0.2 ~ 0.8MPa
Gas consumption	0.6m ³ /min	0.8m ³ /min
Machine Size(mm)	L*W*H=2116*1276*1678	L*W*H=2166*1356*1798
Machine weight	590Kg	730Kg