



KDT-450 Horizontal Flow Wrapper Pack Machine



Main performance and structure features

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. Human-machine operation, convenient and quick parameter setting.
3. Self diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking, digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
7. Simple driving system, reliable working, convenient maintenance.
8. All the controls are achieved by software, convenient for function adjusting and upgrading.

Application

It is especially suitable for packing blisters into pillow bags in pharmaceutical industry.

Also it is suitable for packing regular objects such as biscuit, bread, instant noodle, moon cakes, industrial parts, paper box or trays.

Optional device

1. Code applying machine
2. Line sealing wheel
3. Moire terminal sealing mould
4. Extra big screen

Technical Parameters

Type	KDT-450
Film width	Max.450mm
Bag length	150-450mm
Bag width	30-190mm
Product height	Max.80mm
Film roll diameter	Max. 320mm
Packaging rate	40-180bags/min
Power	220V,50/60HZ,2.8KVA
Machine size	(L)4020X(W)800X(H)450mm
Machine quality	about 580kg