



DASE-SING GROUP

Auto Sleeving Machine DSVC-450PII



MACHINE FEATURES

- 1.Can be fully integrated within production line.
- 2. Safety guards and color touch panel control system ensure unit is user friendly.
- 3.Specially designed cutter plate does not need changing within rated specifications. If necessary,changes can be accomplished in only three minutes.
- 4.Forceful insertion designs could lower producing cost for you.
- 5.Integrated adjustment design for the entire transmission maximizes versatility for accommodating different label specifications.
- 6.Accommodates film paper core size from 5"-10" with variable adjustments.
- 7.PLC(Programmable Logic Control) for increased accuracy and speed over conventional controls.

Innovative Features

- 1.Two head mandrels can produce at the same time with production speed up to 600BPM/180mm when two heads are in operation (assuming that the conveyor and feeding system could match up).
- 2.In case machine head no. 1 or head no. 2 is under repair or needs trouble-shooting or label splicing, one head can do the production with 500BPM/180mm speed.
- 3.Machine head no.1 and head no.2 can produce different labels, for example ,one head with body sleeve, the other head with cap sealing , in the same production line at the same time.
- 4.When machine head no.1 is in operation and head no.2 is on standby,but once machine head no.1 is abnormal, head no.2 can start production automatically to keep the same production speed and performance.

Specification

Max speed	600BPM.
Bottle Diameters	φ25mm~φ125mm.
Film Material	PVC /PET /OPS.
Film Width	PVC: 0.035mm~0.08mm, PET: 0.04mm~0.06mm,OPS: 0.04mm~0.06mm .
Machine Size	2214mm*1550mm*2752mm(L*W*H).
Voltage	3P;220V,380V,415V,440V(Choose one from the given selection).

PACKAGING TYPES



Cap
Sealing Type



Overall
Bottle Type



Full Body
Labeling Type



Fixed Middle Body
Labeling Type



Underlap
Labeling Type