

## *APC-T3 Top Face Labeler Machine*



- Label pre-feeding system makes the label feeding stable, stickup smoothly and label position precise.
- Label-feeding adopt tensioning design to ensure that the coding quality, and can accurately control the length and uniformity of the label.
- The label-rolling and label pressing adopt different structure by different bottles shape to ensure the quality of the labeling.
- You can choose the advanced online systems that can monitor, wrong label, non-label, damaged label, lack of print information, and it can automatically reject these bottles.

### **Feature:**

1. Control system: use SIEMENS brand PLC control system, with high stable operation and extremely low failure rate;
2. Operation system: The Top Face Labeler machine control 7 inch touch screen, directly visual interface easy operation, with Chinese and English two kinds language, also rich with the help function and fault display function ;
3. Check system: Use German LEUZE check label sensor, automatic check label station, stable and convenient don't have much higher requirement for worker;
4. Send label system: use SIEMENS high-power servo control system, stable with high speed;
5. PARAMETER SAVE: can save 10 groups labeling parameters, when change bottles, do not need reset parameters, just adjust machine part is ok.
6. Alarm function: such as label spill, label broken or other malfunction during machine working all will alarm and stop working.

7. Machine Material: Top Face Labeler machine and spare parts all use material S304 stainless steel and anodized senior aluminum alloy, with high corrosion resistance and never rust;
8. Labeling way: use the servo send label system to send label on product surface;
9. Low voltage circuit all use the German Schneider brand.

**Data sheet:**

Type	Output	Power supply	Pressure	Consumption air	Net dimensions	Weight
<b>APC-T3</b>	20-120	220V/50HZ/ 0.15kw	0.4	0.2	2000*700* 1400	220