

FF-60/FF-60D Semi Automatic Flat Surface Labeling Machine



FF-60 semi-automatic flat surface labeling machine is applicable for different sizes flat objects one side or two sides labeling. The semi-automatic flat surface labeling machine can fix a coder printer which can print the LOT, EXP, MFD on the label stick before labeling. The semi-automatic flat surface labeling machine is most popular with the factory. It can work for the normal label, gold and silver label and transparent labels.

By using the method of suction and pasting, the label can be pasted on the plane of various workpieces, such as cosmetic flat bottle, packing box, plastic cover, etc. Changing the labeling mechanism can be applied to uneven surface labeling, such as concave surface, arc surface labeling, etc. Changing the fixture can be applied to label various irregular workpieces. It has powerful functions, and can be used for labeling of plane, arc surface and concave plane of various workpieces, and for labeling of irregular workpieces. The labeling standard is accurate and stable. PLC and subdivision stepper motor are used to drive the label, and the standard is accurate; the discharging mechanism is equipped with brake function to ensure the tension of the label and ensure the accuracy of label detection; the belt detour correction mechanism can prevent the label from shifting left and right. It is durable, the circuit and the gas circuit are arranged separately, and the air circuit is equipped with purification device to prevent the moisture from damaging the electrical appliances and prolong the service life of the equipment; the whole machine is made of high-grade aluminum alloy and stainless steel, with firm quality. It is easy to adjust, with adjustable function of high and low stroke. Different height products are labeled without repeated replacement of fixture. Beautiful appearance, using bottom computer white box, with stainless steel and high-grade aluminum alloy, beautiful and generous, improve the equipment grade. It has two labeling control modes: manual / automatic. Workers can choose to use sensor or foot to realize labeling control according to their needs. manual and automatic control buttons are set, and the length of label can be adjusted at will.

Technology data sheet:

Model	FF-60 / FF-60D
Voltage	110V/220V 50HZ/60HZ
Labeling speed	25-50pcs/min
Object diameter	20mm-120mm
Min label size	30mm*40mm
Max label size	60mm*120mm
Label roll inner diameter	76mm
Maximum outside diameter	300mm
Air supply	0.4-0.6 Mpa
Packing size	650mm*450mm*700mm
Net weight	35kgs
Gross weight	37kgs