AGG-4(1-2,5-10,20) Four Needles Ampoule Filling and Sealing Machine



The machine is a new generation of the ampoule drawing, filling and sealing combined equipment for injections. It adopts the rectangular feeding instead of the traditional ampoule feeding methods. In such case, the feeding is steady with no easy broken ampoule. A modern clutch is mouthed under the ampoule feed hopper.

Therefore, the ampoule feeding can be stopped at any time while the machines is still running. So the ampoule lost can be reduced. In the part of stopping filling where changes electromagnetic switch into mechanical switch. It is reliable and durable, bottle reverse and bottle arranging structure are used in the device of bottle outlet. It reduces the broken rate of the finished product.

Technical Parameters

Model	AGG4/1-2	AGG4/5-10	AGG4/20
Specification(ml)	1-2	5-10	20
Capacity (pcs/min)	128-135	95-100	60-70
Power(kw)	0.35	0.75	0.55
Fuel consumption	2-2.5m3/h(gas)0.08- 0.1MPa(LPG)	2-2.5m3/h(gas)0.08- 0.1MPa(LPG)	2-2.5m3/h(gas)0.08- 0.1MPa(LPG)
Combustion-supporting Consumption	0.7m3/h Oxygen 0.1MPa	0.7m3/hOxygen 0.1MPa	0.7m3/h Oxygen 0.1MPa
Outline Dimension(L*W*H)	1500*930*1300	1500*980*1300	1500*980*1300
Machine Weight(kg)	220	220	250
Power Supply	380V 50Hz	380V 50Hz	220V 50Hz