



## ***Sleeve Labeling Machine UT-250***



### **Features:**

All-cover type stainless steel host machine: the whole machine is waterproof as well as rustproof.

Adjustable cutter head: unique cyclotron cut-off, double sided cutting edge with a long service life.

Single positioning centre guide pillar: more stable for label delivery.

Synchronous bottle divider: a more stable transmission for the bottle.

Bottom set label brush: more precision for casting label.

Label-controlling electric-eye shelf: unique combination of tail and electric-eye to improve the precision for cutting off the membrane materials.

Push-button control cabinet: a more humanized operation.

Independent feeding material shelf: the position of the material shelf is optional at will.

### **Electrical Configuration:**

It adopts PLC programmable controller, imported servo motor, servo driver, frequency converter and transducer; also, it adopts the positioning module to ensure the casting label precise, rapid and stable.

### **Applicable Types of Bottles:**

Various kinds of bottle types, for example: round bottle, square bottle, flat bottle, curve bottle and cup-shaped, etc.

**Technique parameter:**

<b>Model</b>	<b>UT-150B</b>	<b>UT-250B</b>
Input Power	1.5KW	3.0KW
Input Voltage	φ3,380/220VAC	φ3,380/220VAC
Production Efficiency	150 (Bottle/min)	250 (Bottle/min)
Size of Host Machine	L2100mm x W850mm x H2000mm	L2100mm x W850mm x H2000mm
Applicable Diameter of Bottle Body	Φ28mm-Φ125mm	Φ28mm-Φ125mm
Applicable Length of Label	30mm-250mm	30mm-250mm
Applicable Thickness of Label	0.03mm-0.13mm	0.03mm-0.13mm
Applicable Internal Diameter of Paper Tube	(Free Adjustment)	(Free Adjustment)