



Bag Packing Machine TP-MDP



With different feeders changed to pack solid, liquid, thick liquid, powder and so on, Doypack machine is suitable for all kinds of the premade bags, such as pillow bag, 3-side, 4-side and 8-side quad seal bags (box pouch), kraft bags and spout bags ect, Product or packing pouch contact parts adopt stainless steel or other materials which accord with the food hygienic requirements, guarantee hygiene and security of the food

MAIN CHARACTERISTICS

1. Easy to operate adopt advanced PLC from Japan Mitsubishi, mate with touch screen and electric control system, the man-machine interface is friendly.
2. Automatic checking: no pouch or pouch open error, no fill, no seal. the bag can be used again, avoid wasting packing materials and raw materials.
3. Safty device: Machine stop at abnormal air pressure, heater disconnection alarm
4. The width of the bags could be adjusted by electrical motor. Press the control-button could adjust the width of clips, easy operation and save time.
5. It matches with the glass safety door. The machine will stop working when you open the door. So that it could protect the safety of operators. At the same time, it could prevent dust.
6. The packing materials loss low, what this machine is used the preformed bag, the bag pattern is perfect and has a high quality of the sealing part, this improved the product specification
7. With different feeders changed to pack solid, liquid, thick liquid, powder and so on
8. The packing bag suits in extensive range, suit for multi-layer compound, monolayer PE, PP and so on Preformed bag made by film and paper.

PARAMETERS

Model	TP-MDP1	TP-MDP2
Bag Width	85-280mm	100-300mm
Bag Length	130-300mm	130-400mm
Bag Type	Stand-up bag, pillow bag	Stand-up bag, pillow bag
Power Supply	220V, 50HZ	220V, 50HZ
Air Consumption	7.0 CFM@80 PSI	7.0 CFM@80 PSI
Pneumatic Parts	PIAB Vacuum Generator, Pneumatics component Airtac from Taiwan	PIAB Vacuum Generator, Pneumatics component Airtac from Taiwan