



MB-240-2LRS Two Line Roll Sealed Powdered Machine



Suitable for packing granules, such as condiments, sugar, coffee, pepper and so on.

Characteristic:

1. Double four sealing, piston material.
2. Automatic bag making, measuring, cutting, sealing, cutting, counting, printing batch number and other functions.
3. The use of advanced microcomputer controller, drive stepper motor control bag length, stable performance, convenient adjustment, accurate detection.
4. The use of intelligent temperature controller, PID adjustment, to ensure that the temperature range of error control within 1 degrees celsius.

Packaging:

Polypropylene / polyethylene, aluminum foil / polyethylene, polyester / aluminum / polyethylene, nylon / reinforced polyethylene, Paper / polyethylene, filter paper, etc.

| Model | MB-240-2LRS |
|---|--|
| Packing speed | 30-40 bag/min |
| Single bag size | L 30-100mm * W35-70mm (Other specification available upon request) |
| Bag making mode | Four side sealed |
| Range of measuring | 1-15g/bag (Other specification available upon request) |
| The maximum width of inner bag packing film | 240mm |
| Thickness of film | 0.04-0.08mm |
| Main power/voltage | 3KW/220V 50-60Hz |
| Dimension | 600 x 700 x 1800mm |
| The weight of switchboard | 350kg |