

## 2 in 1 Sealing and Shrinking Packager FM-4030A/FM-5540A



## Features:

- 2 IN 1 sealing & shrinking packager is one of the smallest among SBWPACK packaging machines
- Available in the desktop version or equipped with trolley, design with casters for easy mobility. These models are suitable for companies requiring medium to small productions
- Operation of the Chamber Shrink System is simple. The product to be wrapped is placed in the fold film and then set into the chamber. The lid is closed which activates the L-bar sealer and circulates hot air around the package within the chamber, shrinking the film.
- When the package is tight enough simply lift the lid and remove the wrapped package. The
  simplicity, reduced overall size and the extreme versatility of the 2 IN 1 sealing & shrinking
  packager are its best features, as well as high reliability, great performance and low power
  consumption, which make the 2 IN 1 sealing & shrinking packager a smart alternative to
  basic bar seal and heat gun systems

## Scope:

For food, beverages, pharmaceuticals, cosmetics, pesticides and other industries glass bottles, plastic bottles, cups and other containers, bottle or cup body heat shrinkable sleeve label after label

## Specifications:

| Model  | FM-4030                  | FM-5540                  | FM-5540A                 | FM-8060                  |
|--|--------------------------|--------------------------|--------------------------|--------------------------|
| Machine<br>dimension L×W×H(mm)                                       | 1202×568×1005            | 1370×670×1080            | 2022×722×1087            | 1853×1011×1093           |
| Max packing sizeL+H(mm)<br>H<150<br>Max packing sizeW+H(mm)<br>H<150 | ≤350<br>≤250             | ≤450<br>≤330             | ≤450<br>≤330             | ≤700<br>≤500             |
| Max sealing size(mm)   | 400×300                  | 500×400                  | 500×400                  | 800×600                  |
| Packing speed ( pcs/h)   | 500-800                  | 500-800                  | 800-1000                 | 500-800                  |
| Net weight (kg)  | 115                      | 130                      | 140                      | 250                      |
| Power (kw)   | 3.8                      | 4.8                      | 5                        | 6.5                      |
| Power supply   | 1PH 110V/220V<br>50/60Hz | 1PH 110V/220V<br>50/60Hz | 1PH 110V/220V<br>50/60Hz | 1PH 110V/220V<br>50/60Hz |
| Applicable film  | POF/PVC                  | POF/PVC                  | POFIPVO                  |                          |