

## *Biscuit Pillow Packing Machine HTL-280B/280C/280D/280E*



Suitable for packing regular objects such as biscuit, egg pie, bread, chocolate, candy, instant noodle, moon cakes, hardware, daily consuming ware, industrial parts, paper box or trays.

### **Characteristics:**

- 1) It uses servomotor, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and films.
- 2) Human-machine operation, convenient and quick parameter setting.
- 3) Self diagnosis failure function, clear failure display.
- 4) High sensitivity optical electric color mark tracking, digital input cut position which makes the sealing and cutting more accurate.
- 5) Separate PID control to temperature, suitable for various packing materials.
- 6) Stopping the machine in selected position, no sticking to the knife and no waste packing film.
- 7) Simple driving system, reliable working, convenient maintenance.
- 8) All the controls are achieved by software, convenient for function adjusting and upgrading.

### **Specifications:**

<b>Model</b>	<b>HTL-280B</b>
Film width	Max.280mm
Bag length	40-330mm
Bag width	30-140mm
Product height	Max.50mm
Packing speed	50-250 bag/min
Voltage	220V/ 50HZ
Power	2.5kw
Dimension	(L)4000×(W)950×(H)1450mm
Total weight	650Kg
Remark	Can be added printer and air device(OPTION)

<b>Model</b>	<b>HTL-280E</b>
Film width	Max.180mm
Bag length	50-115mm OR 45-90mm
Bag width	30-80mm
Product height	Max.35mm
Rewind diameter	Max.280mm
Packing speed	100-350 bag/min
Voltage	220V/ 380V 50HZ
Power	2.5kw
Dimension	(L)4000×(W)950×(H)1450mm
Total weight	800Kg
Remark	Can be added printer and air device(OPTION)

<b>Model</b>	<b>HTL-280C</b>
Film width	Max.240mm
Bag length	65-190mm OR 120-280mm
Bag width	30-110mm
Product height	Max.50mm
Rewind diameter	Max. 280mm
Packing speed	50-280 bag/min
Voltage	220V/ 50HZ
Power	2.5kw
Dimension	(L)4000×(W)950×(H)1450mm
Total weight	800Kg
Remark	Can be added with printer and air device(OPTION)