

Link-50AD Automatic Flaps Folding Carton Sealing Packing Machine



Link-50AD case sealing and baling machine is driven by belts on both sides, adopts sticky tape to seal, and manually folds the top and bottom to seal the case. Simple, fast and convenient, it can replace labor, improve production efficiency by up to 80%, and save 510% of consumables. It is a good choice for enterprises to save costs, improve production efficiency and realize packaging standardization. The carton sealing and packing machine is also known as the packing and sealing machine, and the sealing and packing machine is manually adjusted according to the size of the carton.

Features of carton sealing machine:

.Manufactured with international advanced technology, and selected imported parts and electrical components;

The main color of this box sealing machine is red, and it can also be customized according to customer needs;

- .The sealing and baling machine can manually adjust the width and height according to the carton specifications;
- · Manually fold the upper cover, and seal the box with the upper and lower characters at one time;
- ·It can be used with different types of automatic balers;
- ·Equipped with blade guard. Avoid accidental stabbing during operation;

It can be customized, can be operated on a stand-alone machine, or can be used in conjunction with an automated packaging line. It is the choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization.

Application range of sealing machine:

Relying on the above advantages, the sealing and packing machine is widely used in food, medicine, beverage, tobacco, daily chemical, hardware, toys, electronics and other industries at home and abroad.

Technical Parameters:

Model	Link-50AD
Applicable to the power supply	380 v / 50 hz / 0.4 KW
Minimum packing size	L 250 * W 120 * H 130mm
Maximum packing size	L unlimited * W 500 * H 500mm
Mesa height	H450-700mm (adjustable)
The belt speed	20 m/min
Packing tape	Brown paper tape, BOPP tape
Tape size	W48, 60, 75 mm
Packing tape requirements	Thickness of 0.6 ~ 0.8 mm * 12 ~ 15 mm wide
Installation dimensions	L1300 * W900 * H 1375mm
The net weight	130Kg