

DXDF60II Pillow-Bag Packaging Machine



The process of measuring, bag-making, filling, sealing, printing and cutting can be done automatically.

The packaging machine can pack many kinds of material such as grain, powder, liquid and tablet, etc.

Packaging Material:

Various Laminate Film, for example: Polypropylene / Polythene, Polyester/Aluminium foil/Polythene, Polyester/Aluminium-plating/Polythene, Nylon/ Polythene, Polyester/Polythene, etc.

Technical Features:

1. Adopts CPU to control each function states, and setup the man-machine conversation interface.
2. The Double channel temperature of the horizontal and vertical is controlled by intelligent temperature controlling device.
3. Intelligent photo cell orientation, transform discretionarily between the light/shade. Strongly anti-jamming, when two bags can't catch up with the upper mark the machine will stop and give an alarm.
4. The packaging speed can be adjusted continuously within specified range. Orientation open mouth and stop.
5. The bag-making has high precision. Easily Operation and maintain.
6. Measurement adopts adjustable cup method, which is accorded with the national measurement standard.

Purpose:

Powder kind: Milk powder, bean powder, condiment, humid pesticide powder, etc.

Technical Parameter:

- Pouch length: 50~140 mm
- Pouch width: 50~100 mm
- Packing speed: 40~60 Bag/min (Depend on the material and specifications)
- Seal Style: Pillow
- Filling Capacity: 10~150 ml
- Measuring Method: Auger
- Power consumption: Approx. 1.24 Kw / AC380V
- Dimension: 780 mm(L)x 570 mm(W)x 1650 mm(H)
- Weight: Approx.230 Kg