

## *Horizontal Case Erector Machine WKD-WKX25/WKD-WKX40*



### **Features:**

1. Rationally designed, the forming, folding and sealing process are accomplished simultaneously.
2. Cutter Safety system to prevent hands from stabbed by the cutter.
3. Heavy duty built, both steel and stainless steel types.
4. Equipped with PLC(Siemens) system, saving labor and easy to operate.
5. Adopted international advanced technology, with imported parts and electrical components, this machine has a stable performance and long life-using.

### **Description:**

- World advanced technology introduced during manufacturing, imported electrical and pneumatic components applied;
- Cam continuous system applied, and machine running precisely, stably and wear resultantly;
- Frequency converter applied for case forming and sealing, thus, speed can be randomly adjusted to save manhour;
- Simple operation, easy adjustment, no worry about case damage;
- Case blank horizontally stored and can be reloaded at any time without power off the machine;
- Automatically pre-warning and reminding for case blank reloading;
- Machine will be automatically stopped to avoid any operational injury if transparent acrylic door is opened;
- Beacon alarming for lack of case blank or tape;
- Can be used alone or integrated to a packaging line.

## Configuration:

1. Good quality bearing.
2. CHIN safety switch, Double insurance, safety and reliable.

## Specifications:

Model	WKD-WKX25	WKD-WKX40
Power	220V, 1P, 50Hz, 800W	
Air pressure&consumption	0.6MPa, 450nl/min	
Machine size	L2580*W1150*H1800mm	L3120*W1250*H1740mm
Machine weight	1200kg	
Case size	L+W≤900mm; W≤400mm; H+1/2W≤530mm; 1/2W≤200mm	
Initially stored cardboard quantity	70~100pcs	
Tape size	(48~72mm)*900	
Erecting speed	≤25 cases/min	≤40 cases/min
Worktable H	900~950mm	