

## ***WP-ES Series Side Seal Vertical Packaging Machine***



### **Application**

- ◎ Applicable bag type: Three side seal bag, Four side seal bag.
- ◎ Applicable film materials: A variety of laminated films, single-layer PE film, film thickness range 0.03mm~0.15mm.
- ◎ Applicable packing materials: A variety of snack food, chemical material, medicine, milk powder, coffee, oatmeal, granulated sugar, salt, puffed food, rice, herbal, tea, small hardware etc.

### **Feature**

- ◎ Double servo motor driving, optical tracking devices, parameter control to adjust the bag length (encoder is optional), mechanical coding adjustment.
- ◎ Panasonic PLC control, man machine interface.
- ◎ Easy to operate, low maintenance, compatible with a variety of different devices.
- ◎ One-piece horizontal seal, gas driving, no repeatedly press to keep edge elegant.
- ◎ Horizontal seal is designed with a pneumatic finger clip bag structure keep seal flat.
- ◎ Three speed level control.
- ◎ Strict safety protection, door shutdown function, no film alarm function, and no ribbon alarm.
- ◎ 304stainless steel frame.

## Technical Parameters

Model	WP-ES3220	WP-ES4230
Film Width	120 ~ 320mm	150-420
Bag Size	L*W=(40-210)*(60-160) mm	L*W=(60-300)*(75-210) mm
Sealing width	5 ~ 10mm	5 ~ 10mm
Packing Speed	60bags/min	50bags/min
Horizontal sealing driven system	cylinder	cylinder
Film pulling driven system	cylinder	cylinder
Voltage	2.4KW/220V/50(60)HZ	3.5KW/220V/50(60)HZ
Gas Pressure	0.2 ~ 0.8MPa	0.2 ~ 0.8MPa
Gas consumption	0.6m <sup>3</sup> /min	0.6m <sup>3</sup> /min
Machine Size(mm)	L*W*H=1326*1066*1503	L*W*H=1208*1030*1620
Machine weight	450Kg	450Kg