



WU-HSING ELECTRONICS CO., LTD.
since 1991

WN-T Series Double-sided Sealing Impulse Sealer



WU-HSING's brand Foot type Double-sides Impulse sealers (WN-T) are made of Alum. housing with powder coating. Are installed twin elements on up & down sealing bars.

Impulse sealing with Timer control (0-2 sec.) , Congealing time is necessary for perfect sealing. Equipped a plug in Timer set (2's) to avoid powder, water to damage the control system.

Equipped with a single or double selecting switch: single sealing (for PE, PP, most of plastic materials), or double-sides sealing (for plastic, Alum. Nylon, Kraft paper bags, and Gusset bags.). Sealing for leak-proof and moisture-proof to protect products.

By foot operated is easier for user to operate machine by foot while 2 hands hold the bags well operated to make an excellent and perfect sealing.

Sealing width: 5.0mm

Sealing time: 0-2 sec.

Congealing time: accordance with the Timer setting.

Optional: Stainless housing (SUS#304), 10mm sealing width, Date Imprinter.

Related sealer: WN series for solid and dry products...

WF series for powder, frozen products, salted products...

W-D Direct Heat sealer for Nylon, Alum., ...

Applications: food, electronics, chemicals, pharmaceutical, and hardware components industries

Specification

| Specification | WN-305T | WN-755T | WN-605T | WN-455T |
|---------------|---------------------|------------|------------|------------|
| Voltage | 110V/220V/230V/240V | | | |
| Power (Watt.) | 1300W | 4000W | 2900W | 2400W |
| Max. sealing | 300*5mm | 750*5mm | 600*5mm | 450*5mm |
| Heating Time | 0-2.0 sec | | | |
| Max. Temp | 250°C | | | |
| Dimension | 38*37*90cm | 83*37*90cm | 68*37*90cm | 53*37*90cm |
| Weight | 20KG | 28KG | 25KG | 22KG |