



Automatic Quantitative Filling and Packaging Machine JS-8



Product Features:

- Photo-cell controlled, ensure extremely accurate bag forming, sealing and cutting performance.
 - This unit can perform either three sides sealing, four sides sealing or pillow type packaging. Specify desired packing choice when ordering.
 - Equipped with a product counting device.
 - All components in direct contact with the product are made of stainless steel, conforming to sanitary standards.
 - Convenient package size & packing speed are adjustable. Adjustment can be made while the machine is running.
 - The entire procedure from weighing, bag forming, filling and sealing to cutting and packaging is fully automatically operated.
 - Date coder available on request.
 - Machine can equip vibration loading system according to the packaging product characteristic.
 - Machines can be made to customers' own specifications on request.
-
- Applicable packing products: Powders, granules, tablets... etc...Such as sugar, salt, tea, beans, medicine, health foods, melon seeds... etc.
 - Applicable packing materials: Poly-Cello. PET+PE+Aluminum Foil+PE,OPP+PE, Aluminum Foil+PE and other heat sealable materials.
 - Standard Equipment: Tool box containing: 1 x Box wrench. 1 x Hexagonal Wrench. 1 x Screwdriver.
 - Optional Equipment: Automatic quantity warning device. Automatic Date Coder. Easy opening device. Input conveyor. Output conveyor.

Specifications:

Packaging type (One option only)	3 sides sealing, 4 sides sealing or pillow type packaging
Packaging weight	100-600g (varies with product density)
Packaging size	Packing film width (W) 200-360mm
	Bag length (L) 120-240mm
	(Specifications available upon request)
Packaging speed	About 20-50 bags/min
Motor	1/4 HP (Main drive)
	1/25 Hp (Controller)
Power supply	110/220V, 50/60HZ single phase (can be made upon request)
Machine dimensions (L x W x H)	165 x 120 x 230 cm (Approximately)
Packing dimensions (L x W x H)	185 x 140 x 215 cm (Approximately)
Net weight	860 kgs
Gross weight	980 kgs