

## *JY-280F / JY-320F Automatic Flow Wrapping Machine*



### **Main performance & characteristics**

1. Adopt a higher precision Servo system, with PLC & AC inverter intelligent and step-less controlling which can realize simple operation and more correctly cutting.
2. High-sensitive photo sensor, automatically adjusts, track, find cutting point, and accumulatively count packs, Automatic measure bag length.
3. Digital and independent PID temperature controlling, suitable for various packing materials. New type double fin sealing design makes the packaging high efficiency and beauty.
4. Adjustable bag former and pitches, enable the change of packing products conveniently.
5. The area connect to products are full stainless steel .With timing belt transmission, Compact structure, lower noise and less shake.
6. Variety of optional device is available, Like: Touch screen/Date coder/Labels applicator/Euro slot or hole punch/Gusset forming /Nitrogen or gas inflation/Spraying alcohol/Automatic film splicer/ Auto feeding/Desiccant feeder /Auto falling/Products conveyor/No products no packing | Check weigh / Metal detector etc.

### **Using range:**

Mainly used for various kinds of solid objects with regular shape (Square/Rectangle/Circular/Ellipse/Flake etc.), such as moon-cake, muffin cake, bread, fruit pie, biscuits, sweet roll, sweets, chocolate, pharmaceuticals tools, medicine, daily necessities, hardware, or any other products loaded in box or tray.

**Technical parameter:**

<b>Model</b>	<b>JY-280F</b>	<b>JY-320F</b>
Packing speed (bag/minute)	30-200bag/min	30-200bag/min
Packing size (mm)	L60-280	L80-320
Length x Width x Height	W10-40/40-100	W10-40/40-100
	H5-25/25-40	H5-30/30-60
Maximum width of film (mm)	<280mm	<320mm
Thickness of film (mm)	≥0.02mm	≥0.02mm
Power	220V,50/60HZ,2.5KW	220V,50/60HZ,2.5KW
Overall size (mm)	4390*700*1520mm	4390*700*1520mm
Weight	500kg	550kg
Package	2.2CBM.2CASES	2.3CBM.2CASES
Packing material	OPP/PP、OPP/PP PT/PE、PE、KOP/PP、PT/PE/x AL/PE etc.Any heat-sealable composite materials foil/film	