

## Pillow Bag Packaging Machine



Packaging various kinds of regular objects like biscuits, popcorn cookie, snow cookie, pies, chocolates, bread, instant noodles, moon-cakes, consumer products, industrial parts, paper boxes, plates etc.

### Main Features:

1. Double motor, double Panasonic transducer control and PLC controller, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. Buttoned human-machine screen, Chinese or English displaying, convenient and quick parameter setting.
3. Self-diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking, digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
7. Simple driving system, reliable working, convenient maintenance.
8. All the controls are achieved by software, convenient for function adjusting and upgrading.

### Technical Parameters:

Finished package size	Length	30~500mm
	Width	30~110mm
	Height	5~40mm
Vertical and cross sealing strength(Nuton/mm <sup>2</sup> )		> 15N/mm <sup>2</sup>
Packing speed		5~230Bags/min
Packing film width		80~300mm
Power specification		220V 50/60Hz 2.4KVA
Machine weight		900kg
Overall size(L*W*H)		3780×830×1560mm