

VFFS Pillow/Gusseted/Chained Bagger VD32/VD32A/VD32II



Suitable to pack coffee bean, sugar, salt, spice, potatochip, puffed food, jelly, pet food, snacks, gummy, etc

Features

- A. High speed and efficiency
- B. Famous brand PLC control system, large touch screen, convenient to operate;
- C. Film drawing down system and horizontal sealing controlled by servo motor minimize the loss with complete automatic warn protection function;
- D. High automatic, it can complete the whole packaging process, measuring, filling , sealing, date printing , counting, transporting.
- E. The contact parts with food is made of 304# high quality stainless steel ensure food safety

Technical advantages

- Famous brand PLC control system, wide version touch screen, convenient to operate.
- Film drawing down system and horizontal sealing controlled by servo motor;
- Perfect alarm system to reduce waste;
- It can complete feeding, measuring, filling, sealing, date printing, charging (exhausting), counting, finished product delivery when it equips with feeding and measuring equipment;

Technical Parameters:

Model	VD32 / VD32A	VD32II
Max packing speed	80bags/min	100bags/min
Bag size	(L)50-200mm(W) 60-150mm	
Bag type	Pillow bag, gusseted bag, punching bag, vacuum bag	
Max packaging width	320mm	
Packing film material	BOPP/ CPP, BOPP/VMCPP, BOPP/PE, PET/VMPET/PE, PET/PE,etc	
Film Thickness	0.04-0.09mm	
Air consumption	0.8Mpa 0.3cmb/min	
Voltage	2.2KW 220V 50/60Hz	
Dimension	L1115*W800*H1370mm	
The weight of switchboard	300kg	