

Automatic Back Sealing Flow Pillow Food Packing Machine SUN-D250/350



Function and Characteristic

- 1. Dual inverters control, bag length can be set and cut in one step, saving time and bags.
- 2. Computer interface operation, convenient and quick parameter setting.
- 3. PLC control, stable performance available for upgrade.
- 4. High sensitivity photoelectric eye color tracing, numerical input of cutting sealing position for extra accuracy.
- 5. Temperature independent PID control, more suitable for packaging different materials.
- 6. Self-failure diagnosis, clear failure display; positioned stop function, without knife sticking and film wasting.
- 7. Using double encoder enables stable performance.
- 8. Strengthened blade holder makes compact sealing
- 9. Optional air filling device achieves broad application.
- 10. Selected code system achieves credible Packaging.
- 11. Simple and automatic packaging achieves high speed and saving labor.
- 12. Optional material-cutting proof device, guarantee for using.
- 13. Multipurpose packaging, suitable for various packaging to similar type of product.
- 14. Alternative English display.

Specification:

Model	SUN-D250	SUN-D250
Film width	Max.250mm	Max.350mm
Bag length	65~190 or 120~280mm	65~190 or 120~280mm
Bag width	30~110mm	50~160mm
Product height	Max.40mm	Max.45mm
Film roll diameter	Max.320mm	
Packing rate	40~230bag/min	
Power	220v.50/60HZ,2.4KVA	
Machine size	(L)3770*(W)670*(H)1450	(L)3770*(W)720*(H)1450
Machine weight	800kg	900kg